

Electrical Cabinet MINI-CAB Outdoor Single-phase 120 Vac
 1x 40A + 1x 20A Tandem Branches UL 67 SASD



1101-1128-40 MINI-CAB QOB2 1X40A, 2X20A

Features

- UL67
- Several Breaker Combinations Available
- Compact Form Factor
- Integral Surge Protection
- Wall Mount

Applications

- Small Cells
- 5G Sites
- DAS Systems
- Electrical Main Panels
- Electrical Sub-Panels
- Load Expansion

Description

Electrical cabinet (also known as power distribution box) 1101-1128-40 from Transtector is a UL67 power distribution box that accepts a 120 Vac Single-phase electrical service and distributes power to individual loads via 1x 40A + 1x Tandem 20A circuit breakers. This electrical cabinet is equipped with a state-of-the-art SASD surge protector that provides lightning protection for downstream equipment to support long-term system reliability. Transtector electrical cabinets are available in stock with same day shipping.

Electrical Specifications

Description	Minimum	Typical	Maximum	Units
Service Voltage		120		Vac
Maximum Continuous Operating Voltage (MCOV)				
L - N			150	Vac
SCCR (Short Circuit Current Rating)			10	kAIC
Service Current Rating			60	A
Branch Breaker Rating		1x 40A + 1x Tandem 20A		
Breaker Type		QO		

Surge Protection Specification

Description	Minimum	Typical	Maximum	Units
Surge Protection Technology		SASD		
Protection Modes		L-N		
8/20 μ s Surge Current			10	kA

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications:
[Electrical Cabinet MINI-CAB Outdoor Single-phase 120 Vac 1x 40A + 1x 20A Tandem Branches UL 67 SASD 1101-1128-40](#)

Electrical Cabinet MINI-CAB Outdoor Single-phase 120 Vac
 1x 40A + 1x 20A Tandem Branches UL 67 SASD



1101-1128-40
MINI-CAB QOB2 1X40A, 2X20A

Nominal Discharge Current Rating (In)	5	kA
VPR 8/20 μ s L - N		330 Vpk
SCCR (Short Circuit Current Rating)	10	kAIC

Mechanical Specifications

Size

Outer Height	10.2in	[259.08 mm]
Outer Width	5.3 in	[134.62 mm]
Outer Depth	4.3 in	[109.22mm]
Weight	6 lbs	[2.72 kg]
Enclosure Material and Plating	16 Gauge Steel	

Installation

Mount Type	Wall Mount
Service Wiring Terminals	Compression Lug Copper #14 AWG to #4 AWG Aluminum #12 AWG to #3 AWG
Status Indication Terminals	
3-Position Screw Terminal	#22 AWG to #16 AWG

Environmental Specifications

Temperature Continuous	-20 to +65 deg C
Temperature Momentary	-20 to +65 deg C
NEMA Rating	3R
Humidity	90% non-condensing

Compliance Certifications

UL Listed	UL 67 Listed, UL 1449 4th Ed
-----------	------------------------------

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications:
[Electrical Cabinet MINI-CAB Outdoor Single-phase 120 Vac 1x 40A + 1x 20A Tandem Branches UL 67 SASD 1101-1128-40](#)

Electrical Cabinet MINI-CAB Outdoor Single-phase 120 Vac
1x 40A + 1x 20A Tandem Branches UL 67 SASD

1101-1128-40
MINI-CAB QOB2 1X40A, 2X20A



Transtector Systems specializes in protection of highly sensitive, low voltage equipment through its patented, non-degrading silicon diode technology and custom filters. Our power quality expertise translates into a diverse product offering including AC, DC, and signal applications as well as integrated cabinets, power distribution panels and EMP hardened devices.

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: [Electrical Cabinet MINI-CAB Outdoor Single-phase 120 Vac 1x 40A + 1x 20A Tandem Branches UL 67 SASD 1101-1128-40](https://www.transtector.com/electrical-cabinet-mini-cab-outdoor-single-phase-1101-1128-40-p.aspx)

URL: <https://www.transtector.com/electrical-cabinet-mini-cab-outdoor-single-phase-1101-1128-40-p.aspx>

The information contained in this document is accurate to the best of our knowledge and representative of the part described herein. It may be necessary to make modifications to the part and/or the documentation of the part, in order to implement improvements. Transtector reserves the right to make such changes as required. Unless otherwise stated, all specifications are nominal. Transtector does not make any representation or warranty regarding the suitability of the part described herein for any particular purpose, and Transtector does not assume any liability arising out of the use of any part or documentation.

1101-1128-40 CAD Drawing

