

DC Surge Protector SPD I2R Indoor DIN-Rail 48 Vdc, Single-Mode, 40 kA MOV

1102-014-38-2
 I2R SA 48-40



Features

- MOV Surge Protection
- Visual Suppression Status Indicator
- Dry Contact Remote Annunciation Terminals
- Replaceable Suppression Modules
- DIN-Rail Mount

Applications

- Industrial Automation
- Controls & Sense Loops
- Telecommunications Base Stations
- IT & Data Centers
- Wastewater Treatment
- Rail
- Oil & Gas
- LED Lighting

Description

DC surge protector (also known as SPD or lightning protector) 1102-014-38-2 from Transtector is a DIN-Rail style SPD that utilizes state of the art MOV technology to protect critical equipment that operates on a 48 Vdc electrical service. This surge protector provides effective protection against electrical transient surges that are generated both by external lightning events and by internal switching events and supports long-term system reliability by safely shunting high amounts of transient energy while maintaining a very low clamping voltage. Transtector DC surge protectors are available in stock with same day shipping.

Electrical Specifications

Description	Minimum	Typical	Maximum	Units
Service Voltages		48		Vdc
Maximum Continuous Operating Voltage (MCOV)				
MCOV DC			75	Vdc

Surge Protection Specification

Description	Minimum	Typical	Maximum	Units
Surge Protection Technology		MOV		
Surge Protection Modes		Supply to RET		
Response Time			25	ns
8/20 μ s Surge Current			40	kA
VPL 8/20 μ s L-G			700 @ 20kA	Vpk
Nominal Discharge Surge Current (In)		20		kA

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications:
[DC Surge Protector SPD I2R Indoor DIN-Rail 48 Vdc, Single-Mode, 40 kA MOV 1102-014-38-2](#)

DC Surge Protector SPD I2R Indoor DIN-Rail 48 Vdc, Single-Mode, 40 kA MOV

1102-014-38-2
I2R SA 48-40



Mechanical Specifications

Size

Height	3.54 in	[89.92 mm]
Width	0.69 in	[17.53 mm]
Depth	2.38 in	[60.45 mm]
Weight	0.25 lbs	[113.4 g]

Environmental Specifications

Temperature

Operating Range	-40 to +80 deg C
Storage Range	-40 to +80 deg C
Environmental Protection (IP) Rating	IP20
Humidity	95% non-condensing

Installation

Mount Type	DIN-Rail
Service Wiring Terminal	
Screw Clamp Terminal	#6 AWG Stranded
Service Terminal Wire 2	#4 AWG Solid
Status Indication Terminal	
3-Position Screw Terminal	#22 to #16 AWG

Transtector Systems specializes in protection of highly sensitive, low voltage equipment through its patented, non-degrading silicon diode technology and custom filters. Our power quality expertise translates into a diverse product offering including AC, DC, and signal applications as well as integrated cabinets, power distribution panels and EMP hardened devices.


Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: [DC Surge Protector SPD I2R Indoor DIN-Rail 48 Vdc, Single-Mode, 40 kA MOV 1102-014-38-2](https://www.transtector.com/dc-surge-protector-spd-i2r-indoor-din-1102-014-38-2)

URL: <https://www.transtector.com/dc-surge-protector-spd-i2r-indoor-din-1102-014-38-2-p.aspx>


The information contained in this document is accurate to the best of our knowledge and representative of the part described herein. It may be necessary to make modifications to the part and/or the documentation of the part, in order to implement improvements. Transtector reserves the right to make such changes as required. Unless otherwise stated, all specifications are nominal. Transtector does not make any representation or warranty regarding the suitability of the part described herein for any particular purpose, and Transtector does not assume any liability arising out of the use of any part or documentation.

1102-014-38-2 CAD Drawing


REVISIONS		
REV.	DESCRIPTION	DATE
A	INITIAL RELEASE	1/17/19
		APPROVED DWR




3-POS SCREW TERMINAL PLUG FOR
REMOTE SUPPRESSION STATUS WIRING




REPLACEABLE I2R SUPPRESSION MODULE




VISUAL SUPPRESSION STATUS INDICATOR



DIN-RAIL
MOUNTING FOOT




2X COMPRESSION LUGS
FOR SERVICE WIRING




3.81 [96.9]

.70 [17.8]



2.64 [67.1]



		THE INFORMATION AND DESIGN IN THIS DOCUMENT IS THE PROPERTY OF TRANSECTOR CORPORATION. ALL RIGHTS RESERVED.	
10701 AIRPORT ROAD, HAYDEN, ID, 83835 PHONE: 1.208.635.6400 1.800.882.9110 FAX: 1.208.955.2041 www.transsector.com e-mail: sales@transsector.com		SHEET 1 OF 1 SCALE 1:2	REV A
UNLESS OTHERWISE SPECIFIED LEADING DIMENSIONS ARE INCHES DIMENSIONS IN [] ARE MILLIMETERS	TOLERANCES: .X±.2 [5.08] XX±.01 [.25] XXX±.005 [.13]	FRACTIONS ± 1/32 ANGLES ± 1°	ALL DIMENSIONS SHOWN ARE FOR REFERENCE ONLY. THIRD-ANGLE PROJECTION
	SIZE CAGE A 30992	DRAWN BY HMB	PART NUMBER 1102-014-38-2

THESE COMMODITIES, TECHNOLOGY OR SOFTWARE WERE EXPORTED FROM THE UNITED STATES IN ACCORDANCE WITH THE EXPORT ADMINISTRATION REGULATIONS. DIVERSION CONTRARY TO U.S. LAW PROHIBITED.

T-Rev A