

AC Surge Protector SPD LS PLUS Panel 120/240 Vac Split-Phase MOV 300 kA, UL 1449 4th Ed. Type 1 or Type 2

B39-00-3001 LEA LS PLUS 300 120/240-SP



Features

- UL1449 4th Ed. Type 1/Type 2
- High Capacity MOV Protection
- Suppression Status LEDs

Applications

- Electrical Panelboards
- Industrial Automation
- · Communications Base Stations
- IT & Data Centers
- Switchgear
- Motor Control Centers

- Surge Counter
- Audible Alarm
- Dry Contact Remote Annunciation Wire Leads
- · Automatic Transfer Switches
- Wastewater Treatment
- Oil & Gas
- LED Lighting
- Schools
- Hospitals

Description

AC surge protector (also known as SPD or lightning protector) B39-00-3001 from Transtector is a UL1449 4th Ed. Type 1/Type 2 panel style SPD that utilizes state of the art MOV technology to protect critical equipment that operates on a 120/240 Vac split-phase electrical service. This surge protector provides effective protection against electrical transient surges that are generated both by external lightning events and by internal switching events and supports long-term system reliability by safely shunting high amounts of transient energy while maintaining a very low clamping voltage. Transtector AC surge protectors are available in stock with same day shipping.

Electrical Specifications

Description	Minimum	Typical	Maximum	Units
Service Voltages		120/240		Vac
Service Type		Split-Phase		
Maximum Continuous Operatir	ig Voltage (MCOV)			
L-L			276	Vac
L - N			138	Vac
L-G			138	Vac
N - G			138	Vac

Surge Protection Specification

Description	Minimum	Typical	Maximum	Units
Surge Protection Technology		MOV		

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: AC Surge Protector SPD LS PLUS Panel 120/240 Vac Split-Phase MOV 300 kA, UL 1449 4th Ed. Type 1 or Type 2 B39-00-3001



AC Surge Protector SPD LS PLUS Panel 120/240 Vac Split-Phase MOV 300 kA, UL 1449 4th Ed. Type 1 or Type 2

B39-00-3001 LEA LS PLUS 300 120/240-SP



Protection Modes	L-N, L-G, L-L		
8/20µs Surge Current		300	kA
Nominal Discharge Current Rating (In)	20		kA
VPR 8/20μs			
L-L		1,200	Vpk
L - N		800	Vpk
L-G		900	Vpk
N - G		900	Vpk
Response Time		25	ns
SCCR (Short Circuit Current Rating)	100		kAIC

Mechanical Specifications

Size

Height 20 in [508 mm]
Width 16 in [406.4 mm]
Depth 7 in [177.8 mm]
Weight 42 lbs [19.05 kg]

Environmental Specifications

Temperature Range (Operational) -40 to +65 deg C
Environmental Protection Rating NEMA 3R
Humidity 95% non-condensing

Installation

Service Wiring Terminal
Compression Lug #8 to #10 AWG

Compliance Certifications

UL Compliant
Yes
Certifications
UL 1449 4th Ed. Type 1 or Type 2
IEEE Category C High and B Medium

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: AC Surge Protector SPD LS PLUS Panel 120/240 Vac Split-Phase MOV 300 kA, UL 1449 4th Ed. Type 1 or Type 2 B39-00-3001



AC Surge Protector SPD LS PLUS Panel 120/240 Vac Split-Phase MOV 300 kA, UL 1449 4th Ed. Type 1 or Type 2

B39-00-3001 LEA LS PLUS 300 120/240-SP



Transtector Systems specializes in protection of highly sensitive, low voltage equipment through its patented, non-degrading silicon diode technology and custom filters. Our power quality expertise translates into a diverse product offering including AC, DC, and signal applications as well as integrated cabinets, power distribution panels and EMP hardened devices.

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: AC Surge Protector SPD LS PLUS Panel 120/240 Vac Split-Phase MOV 300 kA, UL 1449 4th Ed. Type 1 or Type 2 B39-00-3001

URL: https://www.transtector.com/ac-surge-protector-spd-ls-plus-panel-b39-00-3001-p.aspx

The information contained in this document is accurate to the best of our knowledge and representative of the part described herein. It may be necessary to make modifications to the part and/or the documentation of the part, in order to implement improvements. Transfector reserves the right to make such changes as required. Unless otherwise stated, all specifications are nominal. Transfector does not make any representation or warranty regarding the suitability of the part described herein for any particular purpose, and Transfector does not assume any liability arising out of the use of any part or documentation.

B39-00-3001 CAD Drawing

