

DC PDU, 2U, DUAL-FEED, 48/24VDC, 450A/
 FEED, 10 BRKR POSITIONS EA BUS



DCPDU2B-D-2X10-450

Features

- Compatible with DCPDU2B Circuit Breakers, ranging from 2.5 to 200 A
- Circuit Breakers are Field-Configurable, no tools required
- 24 / 48 Vdc Inputs and Outputs
- Voltage Polarity Neutral
- 450A Bus Bar Inputs
- Alarm Indicator LEDs
- Form C contacts for Remote Status
- 19" & 23" Universal Mounting Brackets

Applications

- Telecommunications Base Stations
- Land Mobile Radio
- First Responder Sites
- Emergency Management Systems
- Industrial Automation
- Utilities

Description

Rack mount power distribution unit (also known as PDU) DCPDU2B-D-2X10-450 from Transtector is an DC 1RU PDU that accepts a 24 to 48 Vdc 2x DC Feeds electrical service and distributes power to individual loads via 10x outputs per feed 2.5 to 200 A circuit breakers. This rack mount unit equipped with state-of-the-art surge protection that provides lightning protection for downstream equipment to support long-term system reliability. Transtector rack mount PDUs are available in stock with same day shipping. Transtector rack mount PDUs are available in stock with same day shipping.

Electrical Specifications

Description	Minimum	Typical	Maximum	Units
Service Voltage	24		48	Vdc
Output Voltage		48		Vdc
Maximum Continuous Operating Voltage (MCOV)				
Line to Return			60	Vdc
Input Current			900	A
Output Current			900	A
Power Status LEDs				
RED		Breaker Alarm		
GRN		System normal		

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications:
[DC PDU, 2U, DUAL-FEED, 48/24VDC, 450A/FEED, 10 BRKR POSITIONS EA BUS DCPDU2B-D-2X10-450](#)

DC PDU, 2U, DUAL-FEED, 48/24VDC, 450A/
FEED, 10 BRKR POSITIONS EA BUS

DCPDU2B-D-2X10-450

Rack mount DC PDU

Mechanical Specifications

Size

Length	19 in	[482.6 mm]
Width	5.98 in	[151.89 mm]
Height	3.45 in	[87.63 mm]
Weight	12.5 lbs	[5.67 kg]
Enclosure Material and Plating	Steel, Black Powder Coat	

Monitoring and Control

Alarm Relay Type	Form C Contacts
Alarm Relays	0

Installation

Mount Type	19" or 23" rack mount
Service Wiring Terminals	
Bus bar	
Status Indication Terminals	
Spring Clamp Terminals	16 to 26 AWG
Operating Temperature	-10 to +70deg C
Storage Temperature	-40 to +85deg C

Compliance Certifications

UL Compliant	UL 60950-1 2nd Edition
RoHS Compliant	Yes

Transtector Systems specializes in protection of highly sensitive, low voltage equipment through its patented, non-degrading silicon diode technology and custom filters. Our power quality expertise translates into a diverse product offering including AC, DC, and signal applications as well as integrated cabinets, power distribution panels and EMP hardened devices.

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: [DC PDU, 2U, DUAL-FEED, 48/24VDC, 450A/FEED, 10 BRKR POSITIONS EA BUS DCPDU2B-D-2X10-450](#)

URL: <https://www.transtector.com/rack-mount-dc-pdu-rack-mount-pdu-dc pdu2b-d-2x10-450-p.aspx>

The information contained in this document is accurate to the best of our knowledge and representative of the part described herein. It may be necessary to make modifications to the part and/or the documentation of the part, in order to implement improvements. Transtector reserves the right to make such changes as required. Unless otherwise stated, all specifications are nominal. Transtector does not make any representation or warranty regarding the suitability of the part described herein for any particular purpose, and Transtector does not assume any liability arising out of the use of any part or documentation.

DCPDU2B-D-2X10-450 CAD Drawing

