





THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF TRANSTECTOR, INC.. ANY REPRODUCTION IN PART OR WHOLE WITHOUT THE WRITTEN PERMISSION OF TRANSTECTOR, INC. IS PROHIBITED.



REVISION					
ZONE	REV	DESCRIPTION	DATE	CHANGED BY	APPROVED
	A	INITIAL RELEASE	04/19/2023	KGLEBOVA	GUTTADAURO



LENGTH FEET [METER]	BLACK	BLUE	WHITE	GREEN	RED
1.0 [.30]	-	TTA00007BL-01F	TTA00007WH-01F	TTA00007GN-01F	TTA00007RD-01F
2.0 [.61]	-	-	TTA00007WH-02F	TTA00007GN-02F	TTA00007RD-02F
3.0 [.91]	-	-	TTA00007WH-03F	TTA00007GN-03F	TTA00007RD-03F
6.0 [1.83]	TTA00007-06F	TTA00007BL-06F	TTA00007WH-06F	TTA00007GN-06F	TTA00007RD-06F
8.0 [2.44]	-	TTA00007BL-08F	TTA00007WH-08F	-	TTA00007RD-08F

NOTES:

- VOLTAGE RATING: AC \geq 1500V/S
- CONNECTOR C13 POWER RATING: 15A UL-E257089
- CONNECTOR C20 POWER RATING: 15A UL-E257089
- CABLE: SJT 14AWGx3, 300V, 60°C VW-1 E313867 FT1
- CABLE ASSEMBLY SHALL BE INDIVIDUALLY PACKAGED.

UNLESS OTHERWISE SPECIFIED, DIMENSIONS ARE IN INCHES [mm] OVERALL CABLE LENGTH TOLERANCE: ≤ 12 [305] = +1 [25] / -0 > 12 [305] ≤ 60 [1524] = +2 [51] / -0 > 60 [1524] ≤ 120 [3048] = +4 [102] / -0 > 120 [3048] ≤ 300 [7620] = +6 [152] / -0 > 300 [7620] = +5% / -0 ALL OTHER DIMENSIONAL TOLERANCES: .X = $\pm .2$ [5] FRACTIONS $\pm 1/32$.XX = $\pm .02$ [.5] ANGLES $\pm 1^\circ$.XXX = $\pm .005$ [.13]	APPROVALS DRAWN BY KGLEBOVA CHECKED BY DFRISIELLO APPROVED BY GUTTADAURO	DATE 04/05/2023 04/07/2023 04/11/2023	 an INFINITI® brand 10701 Airport Road, Hayden, ID 83835 Phone: 1.208.635.6400 Fax: 1.208.955.2041	CATEGORY POWER PRODUCTS	PRODUCT DESCRIPTION PC/PDU POWER CORD - C20 TO C13 - 15Amp	SCALE: NONE CAD FILE: tta00007-xxx.SLDDRW	SHEET 1 OF 1
	THIRD-ANGLE PROJECTION 	CONFIGURATION DETAILS OF UNDIMENSIONED FEATURES MAY VARY COLOR VARIATIONS MAY OCCUR					