

Installation Instructions

VPR3MCC



an INFINIT[®] company

Warning

1. Read and understand all instructions before installation
2. The ground wire on the suppressor must be attached directly to the metal chassis of the equipment to be protected. The shortest lead length possible is recommended.
3. Verify that the metal chassis of your equipment is connected to ground through a properly grounded AC outlet.
4. This device is not intended to be used as protection against a direct lightning strike.

Thank you for your recent purchase of our surge protection solution. Your satisfaction with our product and service is important to us. If you have any questions, comments or concerns, please contact us at 800.882.9110 or visit our website at www.transtector.com. We look forward to continuing to serve your protection needs.

Installation Instructions

VPR3MCC

Audio Signal Protection Products:

1. De-energize the unprotected equipment.
2. Disconnect the incoming data line from The equipment.
3. Verify that the equipment chassis is attached Through the power cord to an earth ground.
4. Directly attach the protector to the equipment port.
5. Attach the green ground wire to the metal chassis:
 - 5.1 Remove a screw on the metal chassis that is within Reach of the ground wire.
 - 5.2 Remove any paint around the hole surrounding The screw
 - 5.3 Install screw with ground wire under it. Tighten securely.
6. Attach the incoming data line to the protector.
7. Re-energize the protected equipment.

Transtector Model: VPR3MCC Dispatch Console Protector

